

**MODEL STXD-Direct Drive  
CENTRIFUGAL ROOF MOUNTED EXHAUSTER  
STANDARD FEATURES:**

- Aluminum construction
- Vibration isolators
- Motor wire pigtail
- Disconnect (except 2 speed & explosion proof)
- Conduit chase
- Factory test run
- 5 year fan warranty (except UL 762 which has 2 year fan warranty)
- 1 year motor warranty

STXD Model No.	Rated Motor RPM		Rated Motor HP	Explosion Proof 115/230V 1 PH (2) 1725 RPM	ODP	
	60hz	50hz			115/1 60/50 Hz	230/1 60/50 Hz
6C	1550	1290	1/10	-	1301.11Y.15	1301.22Y.15 (A)
6	1550	1290	1/10	-	1301.11Y.15	1301.22Y.15 (A)
7	1550	1290	1/10	-	1301.11Y.15	1301.22Y.15 (A)
812	1050	-	1/25	-	1300.11R.10	-
810	1550	1290	1/10	-	1301.11Y.15	1301.22Y.15 (A)
8	1625	1400	1/4	605712	1309.11Y.17	1309.11Y.17
102511	1075	825	1/4	-	1309.11M.10	1309.11M.10
1033	1625	1400	1/3	605713	1310.11M.17	1310.11M.17
1225	1075	825	1/4	-	1309.11M.10	1309.11M.10
1250	1625	1350	1/2	605714	1311.11M.17	1311.11M.17
1425	1075	825	1/4	-	1309.11M.10	1309.11M.10
1401	1725	-	1	-	605262 (B)	605262 (B)
1550	1140	945	1/2	-	1311.11M.12	1311.11M.12
1515	1725	-	1 1/2	-	605282 (B)	605282 (B)
1650	1140	945	1/2	-	1311.11M.12	1311.11M.12
1615	1725	-	1 1/2	-	605282(B)	605282(B)

All motors shown feature internal **thermal overload protection**.

Models 6C and 6 include an integral choke plate.

Safety disconnects are plug type on 1/10HP & 1/25HP motors only. All others have toggle type.