

**MODEL UBSRD - REMOTE DRIVE  
UPBLAST PROPELLER ROOF EXHAUSTER**

SIZE	HP	OPEN			TE		AVG. WT
		1 PH		3 PH	1 PH	3 PH	
		115	208/230V	(1)	115/208/230V (2)	(1)	
24L	1/2	Y	Y	Y	Y	Y	280
	3/4	Y	Y	Y	Y	Y	280
	1	Y	Y	Y	Y	Y	285
	1 1/2	Y	Y	Y	Y	Y	290
30L	3/4	Y	Y	Y	Y	Y	340
	1	Y	Y	Y	Y	Y	340
	1 1/2	Y	Y	Y	Y	Y	345
	2	Y	Y	Y	Y	Y	345
30H	2	Y	Y	Y	Y	Y	345
	3			Y		Y	365
	5			Y		Y	365
36L	1	Y	Y	Y	Y	Y	400
	1 1/2	Y	Y	Y	Y	Y	405
	2	Y	Y	Y	Y	Y	405
	3			Y		Y	425
36H	3			Y		Y	425
	5			Y		Y	425
42L	1	Y	Y	Y	Y	Y	500
	1 1/2	Y	Y	Y	Y	Y	500
	2	Y	Y	Y	Y	Y	500
	3			Y		Y	520
	5			Y		Y	530
42H	5			Y		Y	530
	7 1/2			Y		Y	530

(1) 208/230/460V. Please specify required voltage.  
(2) 2HP motor is 115/230V. Contact factory for other voltages.

All prices include a motor selected by the manufacturer. If a specific motor brand or specification is needed please contact Customer Service for special list pricing and delivery times.

**ORDER BY SPECIFIC VOLTAGE**

Motors come with Thermal Overload Protection as standard.

**MODEL UBSRD - REMOTE DRIVE  
UPBLAST PROPELLER ROOF EXHAUSTER**

SIZE	HP	OPEN			TE		AVG. WT
		1 PH		3 PH	1 PH	3 PH	
		115	208/230V	(1)	115/208/230V (2)	(1)	
48L	1 1/2	Y	Y	Y	Y	Y	525
	2	Y	Y	Y	Y	Y	525
	3			Y		Y	545
	5			Y		Y	565
48H	5			Y		Y	565
	7 1/2			Y		Y	740
	10			Y		Y	750
54L	1 1/2	Y	Y	Y	Y	Y	640
	2	Y	Y	Y	Y	Y	640
	3			Y		Y	640
	5			Y		Y	650
54H	3			Y		Y	640
	5			Y		Y	650
	7 1/2			Y		Y	820
	10			Y		Y	830
60L	3			Y		Y	705
	5			Y		Y	705
	7 1/2			Y		Y	885
60H	3			Y		Y	705
	5			Y		Y	705
	7 1/2			Y		Y	885
	10			Y		Y	895

(1) 208/230/460V. Please specify required voltage.  
 (2) 2HP motor is 115/230V. Contact factory for other voltages.

All prices include a motor selected by the manufacturer. If a specific motor brand or specification is needed please contact Customer Service for special list pricing and delivery times.

**ORDER BY SPECIFIC VOLTAGE**

Motors come with Thermal Overload Protection as standard.

**MODEL UBSRD-HT - REMOTE DRIVE  
UPBLAST PROPELLER ROOF EXHAUSTER  
for HEAT & SMOKE REMOVAL**

SIZE	HP	OPEN			TE		AVG. WT
		1 PH		3 PH	1 PH	3 PH	
		115	208/230V	(1)	115/208/230V (2)	(1)	
24L	1/2	Y	Y	Y	Y	Y	305
	3/4	Y	Y	Y	Y	Y	305
	1	Y	Y	Y	Y	Y	310
	1 1/2	Y	Y	Y	Y	Y	315
30L	3/4	Y	Y	Y	Y	Y	365
	1	Y	Y	Y	Y	Y	365
	1 1/2	Y	Y	Y	Y	Y	365
	2	Y	Y	Y	Y	Y	365
30H	2	Y	Y	Y	Y	Y	365
	3			Y		Y	390
	5			Y		Y	390
36L	1	Y	Y	Y	Y	Y	425
	1 1/2	Y	Y	Y	Y	Y	430
	2	Y	Y	Y	Y	Y	430
	3			Y		Y	450
36H	3			Y		Y	450
	5			Y		Y	450
42L	1	Y	Y	Y	Y	Y	525
	1 1/2	Y	Y	Y	Y	Y	525
	2	Y	Y	Y	Y	Y	525
	3			Y		Y	545
	5			Y		Y	555
42H	5			Y		Y	555
	7 1/2			Y		Y	555

(1) 208/230/460V. Please specify required voltage.

(2) 2HP motor is 115/230V. Contact factory for other voltages.

All prices include a motor selected by the manufacturer. If a specific motor brand or specification is needed please contact Customer Service for special list pricing and delivery times.

**ORDER BY SPECIFIC VOLTAGE**

Motors come with Thermal Overload Protection as standard.

**MODEL UBSRD-HT - REMOTE DRIVE  
UPBLAST PROPELLER ROOF EXHAUSTER  
for HEAT & SMOKE REMOVAL**

SIZE	HP	OPEN			TE		AVG. WT
		1 PH		3 PH	1 PH	3 PH	
		115	208/230V	(1)	115/208/230V (2)	(1)	
48L	1 1/2	Y	Y	Y	Y	Y	550
	2	Y	Y	Y	Y	Y	550
	3			Y		Y	570
	5			Y		Y	590
48H	5			Y		Y	590
	7 1/2			Y		Y	765
	10			Y		Y	775
54L	1 1/2	Y	Y	Y	Y	Y	665
	2	Y	Y	Y	Y	Y	665
	3			Y		Y	665
	5			Y		Y	675
54H	3			Y		Y	665
	5			Y		Y	675
	7 1/2			Y		Y	845
	10			Y		Y	855
60L	3			Y		Y	730
	5			Y		Y	730
	7 1/2			Y		Y	910
60H	3			Y		Y	730
	5			Y		Y	730
	7 1/2			Y		Y	910
	10			Y		Y	920

(1) 208/230/460V. Please specify required voltage.  
(2) 2HP motor is 115/230V. Contact factory for other voltages.

All prices include a motor selected by the manufacturer. If a specific motor brand or specification is needed please contact Customer Service for special list pricing and delivery times.

**ORDER BY SPECIFIC VOLTAGE**

Motors come with Thermal Overload Protection as standard.

**MODEL UBSRD-HT1 - REMOTE DRIVE  
UPBLAST PROPELLER ROOF EXHAUSTER  
for HEAT & SMOKE REMOVAL**

SIZE	HP	OPEN			TE		AVG. WT
		1 PH		3 PH	1 PH	3 PH	
		115	208/230V	(1)	115/208/230V (2)	(1)	
24L	1/2	Y	Y	Y	Y	Y	330
	3/4	Y	Y	Y	Y	Y	330
	1	Y	Y	Y	Y	Y	335
	1 1/2	Y	Y	Y	Y	Y	340
30L	3/4	Y	Y	Y	Y	Y	390
	1	Y	Y	Y	Y	Y	390
	1 1/2	Y	Y	Y	Y	Y	395
	2	Y	Y	Y	Y	Y	395
30H	2	Y	Y	Y	Y	Y	395
	3			Y		Y	415
	5			Y		Y	415
36L	1	Y	Y	Y	Y	Y	450
	1 1/2	Y	Y	Y	Y	Y	455
	2	Y	Y	Y	Y	Y	455
	3			Y		Y	475
36H	3			Y		Y	475
	5			Y		Y	475
42L	1	Y	Y	Y	Y	Y	550
	1 1/2	Y	Y	Y	Y	Y	550
	2	Y	Y	Y	Y	Y	550
	3			Y		Y	570
	5			Y		Y	580
42H	5			Y		Y	580
	7 1/2			Y		Y	580

(1) 208/230/460V. Please specify required voltage.

(2) 2HP motor is 115/230V. Contact factory for other voltages.

All prices include a motor selected by the manufacturer. If a specific motor brand or specification is needed please contact Customer Service for special list pricing and delivery times.

**ORDER BY SPECIFIC VOLTAGE**

Motors come with Thermal Overload Protection as standard.

**MODEL UBSRD-HT1 - REMOTE DRIVE  
UPBLAST PROPELLER ROOF EXHAUSTER  
for HEAT & SMOKE REMOVAL**

SIZE	HP	OPEN			TE		AVG. WT
		1 PH		3 PH	1 PH	3 PH	
		115	208/230V	(1)	115/208/230V (2)	(1)	
48L	1 1/2	Y	Y	Y	Y	Y	575
	2	Y	Y	Y	Y	Y	575
	3			Y		Y	595
	5			Y		Y	615
48H	5			Y		Y	615
	7 1/2			Y		Y	790
	10			Y		Y	800
54L	1 1/2	Y	Y	Y	Y	Y	690
	2	Y	Y	Y	Y	Y	690
	3			Y		Y	690
	5			Y		Y	700
54H	3			Y		Y	690
	5			Y		Y	700
	7 1/2			Y		Y	870
	10			Y		Y	900
60L	3			Y		Y	755
	5			Y		Y	755
	7 1/2			Y		Y	935
60H	3			Y		Y	755
	5			Y		Y	755
	7 1/2			Y		Y	935
	10			Y		Y	945

(1) 208/230/460V. Please specify required voltage.

(2) 2HP motor is 115/230V. Contact factory for other voltages.

All prices include a motor selected by the manufacturer. If a specific motor brand or specification is needed please contact Customer Service for special list pricing and delivery times.

**ORDER BY SPECIFIC VOLTAGE**

Motors come with Thermal Overload Protection as standard.

**ACCESSORIES**  
**PROP UPBLAST**  
**MODELS: UBSRD, UBSRD-HT and UBSRD-HT1**

ACCESSORY	FAN SIZE						
	24	30	36	42	48	54	60
Cushion close (1)	Y	Y	Y	Y	Y	Y	Y
Magnetic latches (2)	Y	Y	Y	Y	Y	Y	Y
Outlet Guard (3)	Y	Y	Y	Y	Y	Y	Y
Propeller Blade Side Safety Guard (4)	Y	Y	Y	Y	Y	Y	Y
Extended grease line (5)	Y	Y	Y	Y	Y	Y	Y
Noninsulated Belt Tube and Cover (UBSRD only) (6)	Y	Y	Y	Y	Y	Y	Y
8" Flat Pre-fab steel curb (7)	Y	Y	Y	Y	Y	Y	Y
12" Flat Pre-fab steel curb (7)	Y	Y	Y	Y	Y	Y	Y
Curb Cap Adaptor up to 4" (8)	Y	Y	Y	Y	Y	Y	Y
Epoxy (9)	Y	Y	Y	Y	Y	Y	Y
Heresite (10)	Y	Y	Y	Y	Y	Y	Y
Polyamide-Epoxy Coating (formerly Eisenheiss) (11)	Y	Y	Y	Y	Y	Y	Y
Special Color (Paint Chip required) (12)	Y	Y	Y	Y	Y	Y	Y

- (1) **Cushion Close** - Recommended to help quiet door closing. Available on steel doors only.
- (2) **Magnetic Latches** - Recommend to reduce damper door chatter.
- (3) **Outlet Guard** - Prevents birds or objects from entering fan when not in operation.
- (4) **Propeller Blade Side Safety Guard**: ½ x 1" galvanized wire guard. Important: For all nonducted applications, the manufacturer recommends that a safety guard must be installed as a safety precaution for personnel below unit.
- (5) **Extended Grease Line** - Grease lines to bearings.
- (6) **Noninsulated Belt Tube and Cover (UBSRD only)** - Recommended for applications with non-standard air.
- (7) **Prefab Curbs** - Ship FOB supplier. See current curb submittal for details. All welded construction, 18 ga. galvanized steel, 1" semi-rigid thermal insulation, 1-1/2" wood nailer.
- (8) **Curb Cap Adaptor** - 1" increment only and up to 4" max to overall dimensions.

**COATINGS:**

- (9) **Epoxy Coating (Gray Air Dry)** - For use in alkaline type atmosphere (except in acetic and nitric acids). Epoxy forms an excellent hard, heavy film barrier against chemical attack as well as physical damage from direct impact and abrasion. Heat resistant up to 250 degrees F. Price is for out coverage.
- (10) **Heresite** - Protection against salt atmosphere, humidity and mildly corrosive chemical conditions up to 150 degrees F.
- (11) **Polyamide-Epoxy Coating (formerly Eisenheiss)**: A two component waterborne polyamide-epoxy coating that offers a tough, durable finish. Provides excellent protection in severe corrosive, chemical and abrasive environments.
- (12) **Special Color**- For special color paint chip required.