

Louvers

D-HFA-6



- High Performance Alum. Fixed Blade
- 6" High Free Area
- 60% Free Area
- 915 FPM Point of Water Penetration

Ruskin	ELF6375DX
Greenheck	ESD-635
Arrow United	N/A
Nailor	1606DHP
Pottorff	EFD-637


D-HFA-4



- 4" Deep Alum. Drainable
- 56% Free Area
- 901 FPM Point of Water Penetration
- .18" W.G. Pressure Drop @ Water Penetration

Ruskin	ELF375DX
Greenheck	ESD-435
Arrow United	EA-415D
Nailor	1604D
Pottorff	EFD-437

FL-D-6.1



- 6" Deep Alum. Drainable
- 54% Free Area
- 1,250 FPM Max Velocity
- .12" W.G. Pressure Drop

Ruskin	ELF6375DX
Greenheck	ESD-635
Arrow United	EA-615D
Nailor	1606D
Pottorff	EFD-637

XSD-130



- 5" Deep Alum. Wind Driven Rain
- 46% Free Area
- Class B/674 FPM
- .08" W.G. Pressure Drop

Ruskin	EME520DD
Greenheck	EHH-501
Arrow United	EA-520-D
Nailor	1605WD
Pottorff	ECD-545


CEL-D-6



- 6" Deep Alum. Combination
- 49% Free Area
- 1,079 FPM Beginning Point of Water Penetration
- .11" W.G. Pressure Drop

Ruskin	ELC6375DXW
Greenheck	EAC-601
Arrow United	EA-680-D
Nailor	N/A
Pottorff	EXD-645

CFL-D-4



- 4" Deep Alum. Combination Louver/Damper
- 46% Free Area
- 924 FPM Point of Water Penetration
- .07" W.G. Pressure Drop at Water Penetration

Ruskin	ELC445D
Greenheck	EAC-401
Arrow United	EA-480-D
Nailor	1604CD
Pottorff	EXD-437

Top 20 Products

Manual Volume, Control, Backdraft Dampers

CD-100/101



- Extruded Alum. Frame
- 3V Extruded Alum. Blades
- Class 1A Leakage
- 2,600 FPM Max. Velocity

Ruskin	CD51
Greenheck	N/A
Arrow United	506
Nailor	N/A
Pottorff	N/A

CD-110/111



- Galvanized Steel Construction
- 16 ga. 3V Blades
- Class 1A Leakage
- 3,500 FPM Max. Velocity

Ruskin	CD35
Greenheck	VCD-23
Arrow United	1770
Nailor	1020
Pottorff	CD-42

CD-150/151



- Extruded Alum. Construction
- Airfoil Blades
- Class 1A Leakage
- 6,000 FPM Max. Velocity

Ruskin	CD50
Greenheck	VCD-43
Arrow United	AFD-20
Nailor	2020
Pottorff	CD-52

CB-600



- Extruded Aluminum Construction
- 2,800 FPM Max. Velocity
- 3" W.G. Max Pressure
- Optional Field Mount Actuator Kit

Ruskin	BD2/A1
Greenheck	ES-30
Arrow United	500-B
Nailor	1370
Pottorff	BD-150

Model RD



- True Round Control/Balancing Damper
- Galvanized Steel Construction
- 2,600 FPM Max. Velocity
- 3" W.G. Max Pressure

Ruskin	MDRS25
Greenheck	MBDR-50
Arrow United	200VCRD
Nailor	1890
Pottorff	CD-10R

Model RI



- Galvanized Steel Construction
- Bronze Oilite Bearings
- Up to 2,600 FPM
- Up to 6" W.G.
- Optional Factory Install Actuators

Ruskin	CDRS-25
Greenheck	VCDR-50
Nailor	1090
Pottorff	CD-25R

MD-115/116



- Galvanized Steel Construction
- Opposed or Parallel Blades
- 3,500 FPM Max. Velocity
- 4" W.G. Max Pressure

Ruskin	MD-35
Greenheck	MBD-15
Arrow United	1660
Nailor	1820
Pottorff	MD-42

Life Safety


F/S-3V-I



- UL555(S) 1 ½ Hr. Class I
- Single Side Angle - 108"x96"
- Factory Installed Test Switch

Ruskin	FSD37
Greenheck	FSD-211
Arrow United	AR-1
Nailor	1271
Pottorff	FSD-141

C-SR-WT



- UL555C
- UL555 1 hr. Rated
- Factory Plenum Box
- Optional Volume Adjustment

Ruskin	CFD7T
Greenheck	CRD-1WT
Arrow United	N/A
Nailor	0755
Pottorff	CFD-521

F/S-AF-I



- Airfoil Blades
- UL555(S) 1 ½ Hr. Class I
- Single Side Angle - 108"x96"
- Factory Installed Test Switch

Ruskin	FSD60
Greenheck	FSD-311
Arrow United	UA1
Nailor	1220
Pottorff	FSD-151

FDD-ALB



- Dynamic Fire Damper
- UL555 1 ½ hr. Rated
- Single Side Angle - 72"x36" or 36"x72"
- Optional Sleeve Lengths and Gauges

Ruskin	DIBD2
Greenheck	DFD-150
Arrow United	D17A
Nailor	D0110
Pottorff	VFD-10D-A


F/S-3V-II



- UL555(S) 1 ½ Hr. Class II
- Single Side Angle - 108"x96"
- Factory Installed Test Switch

Ruskin	FSD36
Greenheck	FSD-212
Arrow United	AR-2
Nailor	1270
Pottorff	FSD-142


FDD-SALB



- Dynamic Fire Damper
- UL555 1 ½ hr. Rated
- Single Side Angle
- 12" Long Integral Sleeve

Ruskin	DIBD20
Greenheck	DFD-150X12
Arrow United	D17X
Nailor	D0114-12
Pottorff	VFD-10D-A

F/S-AF-II



- Class I Ultra-Low Leakage
- Factory Installed Momentary Test Switch (MTS)
- Rated to 2,000 FPM and 4" W.G.
- Velocities Up to 4,000 FPM and 6" W.G. Available

Pottorff	FSD-151
Greenheck	FSD-311
Nailor	1220 & 1221
Ruskin	FSD60

